



NOTE

PIT COVER TO SATISFY H.20 HIGHWAY LOADING CONDITIONS.

GENERAL NOTES

1. ALL CONCRETE SHALL BE F'c 25Mpa AT 28 DAYS.
2. PITS DEEPER THAN 750mm SHALL BE FITTED WITH GALVANIZED STEP IRONS (SPACE @ 300mm C.T.S) REFER TO STD YSD13 FOR FURTHER DETAILS.
3. THE FLOOR OF THE PIT SHALL BE FORMED UP TO AT LEAST THE SPRINGING LINE.
4. CONCRETE TO BE VIBRATED IN PITS TO ENGINEER SATISFACTION.
5. CONCRETE TO BE POURED INTO PITS DIRECTLY OUT OF SUPPLY VEHICLES.
6. BEDDING MATERIAL SHALL BE 100mm COMPACTED THICKNESS OF CLASS 2 C.R.
7. F72 REINFORCEMENT IN WALLS OVER 2m DEEP.
8. GRATE PERPENDICULAR TO KERB AND CHANNEL.
9. FOR GATIC COVER B145 OR EQUIVALENT REFER MANUFACTURERS STANDARD DRAWING DETAILS.
10. COVER TO BE MADE LEVEL WITH SURFACE OR AS DIRECTED BY THE ENGINEER.
11. CONTRACTOR TO SUPPLY ALL MATERIALS.

Yarra Standard: YSD11
Drawing Title:

JUNCTION PIT WITH GATIC OR EQUIVALENT COVER

Scale at A4 N.T.S
Updated 29/11/07

