



**RESIDENTIAL/DOMESTIC
PROPERTY DRAIN
OUTLET (PD1)**



CIRCULAR HOLLOW SECTIONS
250 STEEL GRADE (TO AS 1163)
NOMINAL OUTSIDE DIAMETER 102
NOMINAL THICKNESS OF 4mm
NOMINAL MASS OF 9.72 kg/m
PIPE TO BE GALVANIZED
OR APPROVED EQUIVALENT

**INDUSTRIAL PROPERTY
DRAIN OUTLET (PD2)**



RECTANGULAR HOLLOW SECTION
250 STEEL GRADE (TO AS 1163)
152*102 NOMINAL OUTSIDE DIMENSIONS
NOMINAL THICKNESS OF 4.9mm
NOMINAL MASS OF 18.6 kg/m
PIPE TO BE GALVANIZED
OR APPROVED EQUIVALENT

SECTION A-A

GENERAL NOTES

1. PIPE TO BE LAID ON A GRADE NO FLATTER THAN 1:100
2. INSTALLATION WORK TO INCLUDE ALL CONNECTIONS AT KERB AND BUILDING LINE
3. ALL CONNECTIONS TO BE INSPECTED & APPROVED BY COUNCIL'S SUPERVISORS BEFORE BACKFILLING.
4. ALL PROPERTY DRAINS TO BE DIRECTED AWAY FROM VEHICLE CROSSINGS.
5. CONNECTIONS NEAR BUILDING LINE TO BE DONE BY CONTRACTOR AS SPECIFIED IN STANDARD DRAWINGS. MODIFICATIONS TO SUIT INDIVIDUAL PROPERTY DRAIN LOCATIONS TO BE DONE BY CONTRACTOR AT NO EXTRA COST.
6. PROPERTY DRAIN TO BE INSTALLED SIMULTANEOUSLY WITH CONCRETE POUR IN NEW KERB AND CHANNEL.
7. PIPES TO BE LAID 90 DEGREES TO THE BUILDING LINE WHENEVER POSSIBLE.
8. WHERE DRAIN IS CONSTRUCTED SEPERATE TO KERB & CHANNEL NEATLY SAW CUT KERB & CHANNEL 100mm EITHER SIDE OF DRAIN & REINSTATE WITH CHARCOAL COLOUR CONCRETE

**Yarra Standard: YSD3
Drawing Title:**

PROPERTY DRAIN OUTLET TO KERB

Scale at A4 N.T.S
Updated 29/11/07

