


RESIDENTIAL/DOMESTIC
PROPERTY DRAIN
OUTLET (PD1)

INDUSTRIAL PROPERTY
DRAIN OUTLET (PD2)



CIRCULAR HOLLOW SECTIONS
250 STEEL GRADE (TO AS 1163)
NOMINAL OUTSIDE DIAMETER 102
NOMINAL THICKNESS OF 4mm
NOMINAL MASS OF 9.72 kg/m
PIPE TO BE GALVANIZED
OR APPROVED EQUIVALENT



RECTANGULAR HOLLOW SECTION
250 STEEL GRADE (TO AS 1163)
152*102 NOMINAL OUTSIDE DIMENSIONS
NOMINAL THICKNESS OF 4.9mm
NOMINAL MASS OF 18.6 kg/m
PIPE TO BE GALVANIZED
OR APPROVED EQUIVALENT

SECTION A-A

GENERAL NOTES

1. PIPE TO BE LAID ON A SLOPE NO FLATTER THAN 1=100
2. INSTALLATION WORK TO INCLUDE ALL CONNECTIONS AT KERB AND BUILDING LINE.
3. ALL PROPERTY DRAINS TO BE DIRECTED AWAY FROM VEHICLE CROSSINGS.
4. ALL CONNECTIONS TO BE INSPECTED & APPROVED BY COUNCIL'S SUPERVISOR BEFORE BACKFILLING
5. PROPERTY DRAIN TO BE INSTALLED SIMULTANEOUSLY WITH CONCRETE POUR IN NEW KERB AND CHANNEL
6. PIPES TO BE LAID 90 DEGREES TO THE BUILDING LINE WHEREVER POSSIBLE.
7. WHERE DRAIN IS CONSTRUCTED SEPERATE TO KERB & CHANNEL NEATLY SAW CUT KERB & CHANNEL 100mm EITHER SIDE OF DRAIN & REINSTATE WITH CHARCOAL COLOUR CONCRETE.
8. THIS STANDARD TO BE USED WHEN RUBBER ADAPTER CONNECTION CANNOT BE USED

Yarra Standard: YSD4 Drawing Title:

PROPERTY DRAIN OUTLET TO KERB
WITH PROPERTY PIT

Scale at A4 N.T.S
Updated 29/11/07

