






-  WEARING COURSE - 30mm THICK SIZE 10 ASPHALT
-  INTERMEDIATE COURSE - 60mm THICK SIZE 20 TYPE N ASPHALT
-  BASE COURSE - 60mm THICK SIZE 20 TYPE N ASPHALT
-  25MPa CHARCOAL COLOURED CONCRETE
-  150mm MIN DEPTH 4% CEMENT TREATED CRUSHED ROCK (CLASS 2).

GENERAL NOTES

1. CHARCOAL COLOURED CONCRETE TO BE F_c 25MPa AT 28 DAYS.
2. CONCRETE TO BE POURED DIRECTLY OUT OF SUPPLY VEHICLE AND VIBRATED TO ENGINEER SATISFACTION.
3. THE 4% CEMENT TREATED C.R SHALL BE LAID WITHIN 15 MINUTES UPON ARRIVAL TO SITE. IT SHOULD BE 4% ABOVE OPTIMUM MOISTURES CONTENT.
4. PREPARATION OF SUBGRADE AS PER VICROADS SPECIFICATION SECTION 204 CLAUSE 204.15.
5. MINIMUM LONGITUDINAL GRADE OF LANE WAY TO BE 0.3%.
6. THE NEED FOR AN A.G PIPE TO BE DETERMINED BY CONTRACT SPECIFICATION OR SUPERVISING ENGINEER.



Yarra Standard: YSD48
Drawing Title:
 TYPICAL LANE WAY : SPOON DRAIN
 WITH ASPHALT FLANKS

Scale : N.T.S
 Updated 12/12/07

