

NOTE

* CONSTRUCT FLAT TOP ASPHALT PAVEMENT BY LAYING 30mm DEEP OF SIZE 10 SAW CUT EXISTING ASPHALT CLASS 320 OVER 70mm DEEP **PAVEMENT AND** OF SIZE 14 TYPE N ASPHALT CLASS 170 CHASE 50mm DEEP 30mm THICK SIZE 10 1000 OR 1500 ASPHALT RAMP RAMP DETAIL **EXISTÍNG** PAVEMENT 70mm THICK SIZE 14 ASPHALT 50mm THICK SIZE 10 ASPHALT 1500 <u>30</u>00 1500 existing pavement

section B-B

GENERAL NOTES

- 1. SIGNS INSTALLATION TO BE ADVISED BY ENGINEER.
- 2. ASPHALT HUMP TO BE CONSTRUCTED IN THREE LAYERS OF SIZE 10 TYPE N ASPHALT
- A SAWCUT CHASE IS REQUIRED AT THE APROACH & DEPARTURE SIDE OF THE HUMP (MINIMUM OF 50mm DEEP BY 300mm wide)
- 4. LINEWORK TO BE ADVISED BY ENGINEER.

Yarra Standard: YSD55 Drawing Title:

FLAT TOP SPEED HUMP

Scale at A4 N.T.S Updated 28/11/07



Richmond Town Hall 333 Bridge Road Richmond PO Box 168 Richmond 3121 Phone (03) 9205 5010 Fax (03) 8417 6666